

The HGUS joist hanger is designed to support trusses and girder trusses from timber members.





[UK-DoP-e06/0270](#), [ETA-06/0270](#)

FEATURES


Material

- Pre-galvanised mild steel.



TECHNICAL DATA

Product Dimensions



References	Joist dimensions [mm]	Product dimensions [mm]						Header holes		Joist holes	
	Width	A	B	C	D	F	t	Ø5x10 Obround	Ø5x10 Obround	Ø6x12 Obround	
HGUS125/80	2x35	80	122	100	66	107	2.5	16	4	8	
HGUS145/80N	2x35	80	145	100	66	107	2.5	22	6	10	
HGUS125/105	2x47	105	110	100	66	107	2.5	16	4	8	
HGUS145/105N	2x47	105	145	100	66	107	2.5	22	6	10	

References	Joist dimensions [mm]	Product dimensions [mm]						Header holes		Joist holes	
	Width	A	B	C	D	F	t	Ø5x10 Obround	Ø5x10 Obround	Ø6x12 Obround	
HGUS145/120	3x35	120	145	100	66	107	2.5	22	6	-	10
HGUS145/155N	3x47	155	145	100	66	107	2.5	22	6	-	10
HGUS48N	89x241	92	180	100	66	107	2.5	28	10	10	-
HGUS410N	89x240 to 457	92	229	100	66	107	2.5	36	10	16	-
HGUS412N	89x300 to 457	92	265	100	66	107	2.5	44	12	20	-
HGUS414N	89x350 to 457	92	316	100	66	107	2.5	52	14	22	-
HGUS180/135	133x200 to 302	135	180	100	66	107	2.5	28	8	10	-
HGUS5.50/10N	133x240 to 457	140	214	100	66	107	2.5	36	10	16	-
HGUS5.50/12	133x300 to 457	140	265	100	66	107	2.5	44	12	20	-
HGUS5.50/14N	133x350 to 457	140	316	100	66	107	2.5	52	14	22	-
HGUS7.25/10	180x240 to 457	184	219	100	66	107	2.5	36	10	16	-
HGUS7.25/12N	180x300 to 457	184	270	100	66	107	2.5	44	112	20	-
HGUS7.25/14	180x350 to 457	184	320	100	66	107	2.5	52	14	22	-

HGUS - Product Capacities

References	Fasteners		Product Characteristic Capacities (TR26 Timbers) [kN]				Safe Working Load [kN]					
	Header	Joist	R _{1,k}		R _{2,k}		R _{1,SWL,Long term}		R _{1,SWL,Medium Term}		R _{2,SWL,Short term}	
	Qty	Qty	CNA4.0x604.0x100mm	CNA4.0x604.0x100mm	CNA4.0x604.0x100mm	CNA4.0x604.0x100mm	CNA4.0x604.0x100mm	CNA4.0x604.0x100mm	CNA4.0x604.0x100mm	CNA4.0x604.0x100mm	CNA4.0x604.0x100mm	
HGUS125/80	20	8	25.1	-	7.8	-	10.1	-	11.5	-	3.9	-
HGUS145/80N	28	10	33.3	-	9.8	-	15.1	-	17.3	-	4.9	-
HGUS125/103	20	8	25.1	-	7.8	-	10.1	-	11.5	-	3.9	-
HGUS145/105N	28	10	33.3	-	9.8	-	15.1	-	17.3	-	4.9	-
HGUS145/120	28	10	33.3	-	9.8	-	15.1	-	17.3	-	4.9	-
HGUS145/155N	28	10	33.3	-	9.8	-	15.1	-	17.3	-	4.9	-
HGUS48N	36	10	-	16.1	-	11.1	-	27.8	-	34.7	-	7.5
HGUS410N	46	16	-	20.5	-	17.7	-	35.1	-	35.1	-	9.7
HGUS412N	56	20	-	26.4	-	22.1	-	40.9	-	40.9	-	11.3
HGUS414N	66	22	-	34.4	-	24.3	-	43.5	-	43.4	-	12.9
HGUS180/135	36	10	-	15.9	-	11.1	-	27.8	-	34.7	-	7.5
HGUS5.50/10N	46	16	-	20.7	-	17.7	-	35.1	-	35.1	-	9.7
HGUS5.50/12	56	20	-	26.6	-	22.1	-	40.9	-	40.9	-	11.3
HGUS5.50/14N	66	22	-	34.6	-	24.3	-	43.4	-	43.4	-	12.9
HGUS7.25/10	46	16	-	21.3	-	17.7	-	35.1	-	35.1	-	9.7
HGUS7.25/12N	56	20	-	27.4	-	22.1	-	40.9	-	40.9	-	11.3
HGUS7.25/14	66	22	-	34.5	-	24.3	-	43.4	-	43.4	-	12.9

HGUS Heavy Engineered Timber Hanger - Manufactured to Order 92-184mm

Reference	Joist dimension [mm]	Product dimensions [mm]					Header holes		Joist holes	Fasteners		Safe Working Load [kN]			
		Width	A	B	C	D	F	Ø5x10 Obround		Ø6x12 Obround	Header Qty	Joist Qty	R ₁ , SWL, Long term	R ₂ , SWL, Medium Term	R ₃ , SWL, Short term
Spec HGUS48N	Variable	92 - 184	180	100	66	107	2.5	28	10	-	36	10	27.8	34.7	7.5

HGUS Heavy Engineered Timber Hanger - Manufactured to Order 185-300mm

Reference	Joist dimension [mm]	Product dimensions [mm]					Header holes		Joist holes	Fasteners		Safe Working Load [kN]			
		Width	A	B	C	D	F	Ø5x10 Obround		Ø6x12 Obround	Header Qty	Joist Qty	R ₁ , SWL, Long term	R ₂ , SWL, Medium Term	R ₃ , SWL, Short term
Spec HGUS48N	Variable	185 - 300	180	100	66	107	2.5	28	10	-	36	10	18.3	20.8	7.5

INSTALLATION

Installation

- Double shear nailing allows distribution of the carried members load through two points on each nail for greater strength.
- Joist nails must be driven at 45° through the joist dome, pan or obround nail holes, into the joist , then the header to achieve the table loads.
- The thickness of the supporting timber must be equal or greater than the fastener length.
- Verify the header can take the required fasteners specified within the table
- Use all specified fasteners.